imagePROGRAF PRO-1100

PRINT WITH CONFIDENCE. ALWAYS





Show your work with Canon's professional A2 printer, delivering deeper blacks and richer blues for fine-art prints that will stand the test of time.

LUCIA PRO II ink **LUCIA PRO II Pigment ink**



12 Single Inks **12 inks**

Connectivity **Wi-Fi and Ethernet connectivity**

3.0 Type (7.5cm) TFT **Colour LCD screen**

Borderless Printing **Borderless printing**



A2 **Prints up to A2**

Canon



Enhanced colours, superior quality

Achieve deeper blacks, richer blues, and smooth colour gradation, thanks to the new[1] 12-colour LUCIA PRO II inks with Chroma Optimiser for smooth reflections and anti-bronzing.



Made to last

Print, exhibit, and sell professional photographs that will resist light damage for 200 years[2]. Rely on industry-leading image robustness to avoid abrasion when shipping or handling prints – all without a compromise on quality.



Versatile and reliable

This A2 printer supports a wide range of paper stocks and sizes, from 420mm in width to 3.27m in length for panoramic prints. Choose from Canon's range of high quality fine-art and photo paper, or opt for third-party media to suits your needs.



Professional printing made easy

Follow on-screen prompts for a simple setup, and connect multiple devices through ethernet or Wi-Fi. Plus, use Canon's Professional Print & Layout software – also available as an Adobe plug-in to suit your existing workflow.



Improved sustainability

The ImagePROGRAF PRO-1100 is produced with renewable energy and delivered with no expanded polystyrene in the box. And you can minimise your waste by sending empty inks to Canon's free cartridge recycling programme[3].

PRODUCT RANGE



PIXMA PRO-200



imagePROGRAF PRO-300



ImagePROGRAF PRO-1100

[1]Eleven out of the twelve inks are newly developed. The matte black is the same as the imagePROGRAF GP-2000/4000.

[2]When using Canon Photo Paper Pro Platinum. Predicted value calculated in accordance with the indoor light resistance test method and life evaluation criteria of the digital colour photographic print image preservation evaluation method (JEITA CP-3901B) published by JEITA (Japan Electronics and Information Technology Industries Association).

[3]Cartridge recycling programme subject to availability in your region.

TECHNICAL SPECIFICATIONS

imagePROGRAF PRO-1100

Class	17"
Ink Type	12 Inks : MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO
Maximum Print Resolution [1]	2,400 x 1,200 dpi
Printing Speed [2]	A2 (LU-101 colour): Approx.3mins 40s A2 (PT-101 colour or mono): Approx. 6mins
Dimensions, Weight	Approx. 723 x 435 x 285 mm Weight approx. 32.4kg (including print head and inks)
Power Supply	AC 100-240V（50-60Hz）
Power Consumption	Printing (Approx. 38W) [3] Standby (Sleep) (Approx. 1.2W) OFF (Approx. 0.1W) Sleep mode (Erp Lot26) Approx. 2.3W
Operational Environment	Temperature: 5-35℃, Humidity: 10-90%RH (no dew condensation) [4]
Acoustic Noise	approx. 42.5 dB(A) - Plain Paper(A4, Color) [5] approx. 43.0 dB(A) - Photo Paper Pro Platinum (PT-201) (4×6, Color, borderless) [6]
Operation Panel Display	3.0" (320 x 240 TFT LCD), Key x 9, LED x 2 22 Languages Selectable: Japanese/English/German/Italian/Spanish/Brazilian Portuguese/Dutch/Polish/Russian/French/Simplified Chinese/Traditional Chinese/Korean/Thai/Indonesian/Turkish Czech/Danish/Swedish/Norwegian/Finnish/Ukrainian
Memory	1GB
INTERFACE TYPE & SOFTWARE	
Supported Operating Systems [7]	Windows 7 SP1, Windows 8.1, Windows 10, Windows 11 Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022 Mac OS OS11.7.10 - OS14 Chrome OS
Supported Mobile Systems	iOS Android
Interface	USB B Port: Hi Speed USB
Protocol	SNMP, HTTP, TCP/IP(IPv4/IPv6)
Wired LAN	
Supported Standards:	IEEE802.3ab (1000BASE-T) / IEEE802.3u (100BASE-TX) / IEEE802.3 (10BASE-T)
Transfer speed:	10Mbps / 100Mbps / 1000Mbps (Auto switching)
Security:	IEEE802.1X(EAP-TLS/EAP-TTLS/PEAP)
Wireless LAN	
Supported Standards:	IEEE802.11n / IEEE802.11g / IEEE802.11b / IEEE802.11a / IEEE802.11ac
2.4GHz Channel	EUM / EMB
5GHz Channel	GB ONLY
Range	Indoor 50M* *depends on the transmission speed and conditions
Security	WPA-PSK(AES) WPA2-PSK(AES) WPA3-SAE(AES) WPA-EAP(AES)* WPA2-EAP(AES)* WPA3-EAP(AES)* * IEEE802.1X(EAP-TLS/EAP-TTLS/PEAP) available
Direct Connection (Wireless Direct)	Available
Smart device & Cloud apps	Canon PRINT app (iOS or Android) Cloud Link Apple AirPrint Mopria for Android
Camera direct	Wi-Fi Pictbridge
Software	Professional Print & Layout
PRINT HEAD	
Type	Canon Bubble-jet on Demand
Head Configuration	12 colors integrated type (4 colors chips x 3)
Nozzle Pitch	600dpi x 2 lines
INK TANK	
Model	LUCIA PRO II Ink Tanks: PFI-4100 MBK/ PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO

Page yield (4x6" PT-101) [8]	Number of 10x15cm photos Matte Black (MBK): 6070 photos* Photo Black (PBK): 2220 photos* Grey (GY): 1870 photos* Photo Grey (PGY): 3685 photos* Photo Cyan (PC): 4785 photos* Cyan (C): 5420 photos* Photo Magenta (PM): 4050 photos Magenta (M): 4735 photos* Yellow (Y): 3415 photos Red (R): 5675 photos* Blue (B): 5580 photos* Chroma Optimizer (CO): 925 photos * Estimated Supplemental Yield
Page yield (A2 PT-101) [8]	Number of A2 colour photos Matte Black (MBK): 1315 photos* Photo Black (PBK): 206 photos* Grey (GY): 133 photos* Photo Grey (PGY): 348 photos* Photo Cyan (PC): 555 photos* Cyan (C): 700 photos* Photo Magenta (PM): 404 photos* Magenta (M): 905 photos* Yellow (Y): 320 photos Red (R): 760 photos* Blue (B): 805 photos* Chroma Optimizer (CO): 90 photos* * Estimated Supplemental Yield
MEDIA HANDLING	
Top Tray	A5, A4, A3, A3+, A2, B5, B4, B3, Letter, Legal, 89 x 127mm (L), 210 x 594mm, KG / 4" X 6" (10 x 15cm), 2L / 5" X 7" (13 x 18cm), 7" X 10" (18 x 25cm), 8" X 10" (20 x 25cm), 9 X 13" (23 x 33cm), 10" X 12" (25 x 30cm), 11" X 14", 11" x 17" (28x443cm), 12" X 12" (30 x 30cm), 13" X 19" (Super B), 14" X 17" (36 x 43cm), 16" x 20", 17" x 22" (43 x 56cm), 17" X 25" (43 x 64cm).
Manual Feed Tray	A4, A3, A3+, A2, B4, B3, Letter, Legal, 210 x 594mm, 8" X 10" (20 x 25cm), 9 X 13" (23 x 33cm), 10" X 12" (25 x 30cm), 11" X 14", 11" x 17" (28x443cm), 12" X 12" (30 x 30cm), 13" X 19" (Super B), 14" X 17" (36 x 43cm), 16" x 20", 17" x 22" (43 x 56cm), 17" X 25" (43 x 64cm).
Paper Size (Borderless)	A4, A3, A3+, A2, B4, B3, Letter, Legal, 210 x 594mm, 8" X 10" (20 x 25cm), 10" X 12" (25 x 30cm), 13" X 19" (Super B), 14" X 17"(36 x 43cm), 17" x 22" (43 x 56cm), 17" X 25" (43 x 64cm).
Supported Media (Top Tray)	Plain Paper, Photo Paper Pro Platinum (PT-101), /Photo Paper Pro Luster (LU-101), Photo Paper Plus Glossy II (PP-201), /Matte Photo Paper (MP-101), Photo Paper Plus Semi-gloss (SG-201), Lightweight Photo Paper, Heavyweight Fine Art Paper, Japanese Paper Washi, Canvas,
Supported Media (Manual Feed Tray)	Photo Paper Pro Platinum (PT-101), Photo Paper Pro Luster (LU-101), Photo Paper Plus Glossy II (PP-201), Matte Photo Paper (MP-101)/ Photo Paper Plus Semi-gloss(SG-201), Premium Fine Art Rough (FA-RG1), Premium Fine Art Smooth (FA-SM1), Lightweight Photo Paper, Heavyweight Photo Paper, Heavyweight Fine Art Paper, Extra Heavyweight Fine Art Paper, Highest Density Fine Art Paper, Japanese Paper Washi, Canvas, Baryta Photo Paper
Media Thickness	Top Tray: Plain paper 64-105g/m^2, Canon specialty paper Max. 300g/m^2, Top Tray: Thickness: 0.1-0.3mm Manual Feed Tray: Canon specialty paper Max. 400g/m^2, Manual Tray Thickness: 0.1-0.7mm
Media Width	Top Tray: 89-432mm, Manual feed slot: 203.2-432mm
Minimal Printable Paper Length	Top Tray: 127mm Manual Feed Tray: 254mm
Maximum Printable Paper Length	3276.70mm
MARGINS (TOP, BOTTOMS, SIDES)	Recommended - Top margin: 57mm, Bottom margin: 55mm, Left/Right: 3.4mm (LTR/LGL: Left margin 6.4mm, Right margin 6.3mm） Printable area -Top margin 3mm, Bottom margin 5mm, Left/Right margin 3.4mm (LTR/LGL: Left margin 6.4mm, Right margin 6.3mm）
Media Width for Borderless Printing [9]	A4, A3, A3+, A2, 4x6", 5x7", 8x10", 10x12", 14x17", 17x22", LTR
CONSUMABLES	
Ink Tank	PFI-4100 MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO (80ml)
Maintenance Cartridge	MC-20

Canon

TECHNICAL SPECIFICATIONS

ImagePROGRAF PRO-1100

Disclaimers

[1] Ink droplets can be placed with a pitch of 1/2400 inch at minimum.
[2] Print speed is based on the default setting using ISO/JIS-SCID N5 and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
[3] When printing ISO/JIS-SCID N2 pattern on A4 size Photo Paper Pro Platinum (PT-101) using default settings.
[4] The performance of the printer may be reduced under certain temperature and humidity conditions.
[5] When printing ISO/JIS-SCID N2 pattern on Photo Paper Pro Platinum using default settings.
[6] Acoustic Noise is measured based on ISO7779 standard.
[7] Minimum system reguirements is according to that of OS and application software used.
[8] Declared yield value in accordance with ISO/IEC 29103. Values obtained by continuous printing.
[9] Paper types NOT supported for borderless printing are as follows: Photo Stickers
Specifications are subject to change without notice.

Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
The Bower
4 Roundwood Avenue
Stockley Park
Uxbridge
UB11 1AF

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2024

PRINT WITH CONFIDENCE. ALWAYS

ImagePROGRAF PRO-1100

Show your work with Canon's professional A2 printer, delivering deeper blacks and richer blues for fine-art prints that will stand the test of time.

Sales Start Date: September 2024



Product details

Product Name	Mercury Code	EAN Code	Recommended Retail Price
imagePROGRAF PRO-1100 GB	6856C005AA	4549292240870	<Please fill in RRP>

Consumables

Product Name	Mercury Code	EAN Code	Recommended Retail Price
Standard size			
PFI-4100M BK	6776C001AA	4549292237955	<Please fill in RRP>
PFI-4100 PBK	6777C001AA	4549292238020	<Please fill in RRP>
PFI-4100 C	6778C001AA	4549292238075	<Please fill in RRP>
PFI-4100 M	6779C001AA	4549292238129	<Please fill in RRP>
PFI-4100 Y	6780C001AA	4549292238174	<Please fill in RRP>
PFI-4100 PC	6781C001AA	4549292238242	<Please fill in RRP>
PFI-4100 PM	6782C001AA	4549292238303	<Please fill in RRP>
PFI-4100 R	6785C001AA	4549292238600	<Please fill in RRP>
PFI-4100 B	6786C001AA	4549292238655	<Please fill in RRP>
PFI-4100 GY	6783C001AA	4549292238501	<Please fill in RRP>
PFI-4100 PGY	6784C001AA	4549292238556	<Please fill in RRP>
PFI-4100 CO	6787C001AA	4549292238709	<Please fill in RRP>
MC-20 OS	0628C002AA	4549292040210	<Please fill in RRP>

PRINT WITH CONFIDENCE. ALWAYS

ImagePROGRAF PRO-1100

Show your work with Canon's professional A2 printer, delivering deeper blacks and richer blues for fine-art prints that will stand the test of time.



Measurement / logistic information

Product Name	Mercury Code	Pack Style	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Gross Weight (kg)	Net Weight (kg)
imagePROGRAF PRO-1100 GB	6856C005AA	Individual	1	960	550	410	38.5	38
		Pallet (Upper)	4	1120	980	970	168.55	385
		Pallet (Bottom)	4	1110	960	830	156.45	385

Canon

PRINT WITH CONFIDENCE. ALWAYS

ImagePROGRAF PRO-1100

Show your work with Canon’s professional A2 printer, delivering deeper blacks and richer blues for fine-art prints that will stand the test of time.



What’s in the box

imagePROGRAF PRO-1100

- imagePROGRAF PRO-1100 A2 printer
- 12 individual ink tanks
- Print head
- Power cord
- Starter guide