## Heavy-duty cutter 846



- · High-quality guillotines for commercial use
- · Solid metal table as a sturdy cutting base
- · Sturdy handle for effortless cutting performance
- · Screw-mounted, ground upper blade for cutting power
- High-quality, re-sharpenable blade made of Solingen steel for long-lasting cutting quality
- Transparent blade cover guards provide reassuring safety while cutting and unobstructed vision the material being cut
- Convenient quick-action clamp for swift results
- Accurately fitting scale bar with mm scale for an exact  $90\ensuremath{^\circ}$  cut
- Spindle-driven, self-locking metal backstop for quickly finding the right format
- Easy-to-change cutting edge can be used for 8 different cutting needs
- · Minimum cut 40 mm
- · Visual line indicator for professional cutting results
- Practical stand with storage shelf with an optimum working height of 74 cm is optionally available (712)
- · Blades can be sharpened
- · Lower frame optionally available
- 1 scale bar



Commercial use: always ready for top performance.



Cutting length 430 mm



Cutting capacity 60.0 mm



Cutting capacity 600 sheets



Table size (overall dimensions) 760 x 650 mm



Carries the GS DGUV (German Statutory Accident Insurance Association) test mark



Extended 5-year guarantee (except wearing parts)



German Engineering by Dahle


Article number	Cutting length in mm	DIN	Cutting capacity in mm	Cutting capacity A4 80 g/sm*	Table size, ex-ternal dimensions, in mm	Off-cut side area, mm	Cut- ting side area, mm	Colours	EAN
00846-21143	430	A3	60	600	760 mm x 650 mm	430 x 430	430 x 215		4007885008462




## Heavy-duty cutter 846




Transparent blade cover guards provide reassuring safety and unobstructed vision while cutting



Lockable hand crank for adjusting the spindle-driven backstop



Convenient quick-action clamp for swift results



Large quantities of paper can be cut with effortless ease

For yderligere oplysninger besøg www.dahle.dk / www.cabi.dk eller ring 30506210

